



ELSEVIER

Contents lists available at ScienceDirect

Mechanical Systems and Signal Processing

journal homepage: www.elsevier.com/locate/ymssp

Potential of neuro-fuzzy methodology to estimate noise level of wind turbines



Vlastimir Nikolić^a, Dalibor Petković^{a,*}, Por Lip Yee^b,
Shahaboddin Shamshirband^b, Mazdak Zamani^c,
Žarko Čojbašić^a, Shervin Motamedi^d

^a University of Niš, Faculty of Mechanical Engineering, Department for Mechatronics and Control, Aleksandra Medvedeva 14, 18000 Niš, Serbia

^b Department of Computer System and Technology, Faculty of Computer Science and Information Technology, University of Malaya, 50603 Kuala Lumpur, Malaysia

^c Advanced Informatics School (AIS), Universiti Teknologi Malaysia, Kuala Lumpur, Malaysia

^d Institute of Ocean and Earth Sciences, University of Malaya, 50603 Kuala Lumpur, Malaysia

ARTICLE INFO

Article history:

Received 26 November 2014

Received in revised form

24 March 2015

Accepted 1 May 2015

Available online 23 May 2015

Keywords:

Wind turbine noise

Sound power level

Noises assessment

Neuro-fuzzy

ANFIS

ABSTRACT

Wind turbines noise effect became large problem because of increasing of wind farms numbers since renewable energy becomes the most influential energy sources. However, wind turbine noise generation and propagation is not understandable in all aspects. Mechanical noise of wind turbines can be ignored since aerodynamic noise of wind turbine blades is the main source of the noise generation. Numerical simulations of the noise effects of the wind turbine can be very challenging task. Therefore in this article soft computing method is used to evaluate noise level of wind turbines. The main goal of the study is to estimate wind turbine noise in regard of wind speed at different heights and for different sound frequency. Adaptive neuro-fuzzy inference system (ANFIS) is used to estimate the wind turbine noise levels.

© 2015 Elsevier Ltd. All rights reserved.

1. Introduction

Wind turbine (WT) noise effect can be considered as one of the main technical issue to the implementation of WT. There are two noise sources of WT, mechanical and aerodynamic noise. Mechanical noise can be dropped by structuring of the mechanical components. On the other hand, the aerodynamic noise is very challenging task to overcome. There are two types of the aerodynamic noises: discrete (tonal) and broadband noise. Tonal noise low frequency noise and it is generated by the movement of WT blades which caused disturbance in flow. On the other hand, the broadband noise, which is higher frequency noise, is generated by turbulent flows. It is needed to predict and estimate aerodynamic noise of WT in order to reduce the noise.

Many researchers investigated the WT noises so far. The change of WT noise due to blade flexibility was investigated in [1]. It was shown that the more flexibly blades produces less noise. In article [2] the turbulence effect of the noise generation was analysed. One numerical method for prediction of the WT noise was developed in [3] which were based on Reynolds-averaged Navier–Stokes (RANS) based solver. Another numerical method based on Ray theory was used to characterize the WT noise

* Corresponding author. Tel.: +381 643283048.

E-mail address: dalibortc@gmail.com (D. Petković).